

1.

- 1.1
- 1.2

GB 50058

GB 5226.1

GB/T 3811

1.3

2.

- 2.1

| 1  | A02 | 1 | 14.6<br>+ | 1 |
|----|-----|---|-----------|---|
| 2  | A03 |   |           | 1 |
| 3  | A04 |   |           | 1 |
| 4  | A07 |   |           | 1 |
| 5  | A27 |   |           | 1 |
| 6  | A30 |   |           | 1 |
| 7  | B20 |   |           | 1 |
| 8  | B23 |   |           | 1 |
| 9  | B27 |   |           | 1 |
| 10 | B34 |   |           | 1 |
| 11 | B37 |   |           | 1 |
| 12 | D15 |   |           | 1 |
| 13 | D16 |   |           | 1 |
| 14 | D20 |   |           | 1 |
| 15 | D21 |   |           | 1 |

---

2.2

2.3

2.4

2.5

3

220/380V    10%    50Hz    1%

4

|   |  |    |  |
|---|--|----|--|
|   |  |    |  |
| 1 |  | 7  |  |
| 2 |  | 35 |  |
| 3 |  |    |  |
| 4 |  | 5  |  |
| 5 |  | 5  |  |

5

5.1

+                    /

5.2

800 kg (4                    +                    +                    )

5.3

---

(L)

(W)

(H) 4.6

500 mm( )

5.4 / 5 m/min 10%

5.5 / ( ) / ( )

5.6

Ex d IIB T4 Gb

/

1050mm

5MM

5.7

○

Sa2.5

○

( 70 m)

○

( 100 m)

○

( 70 m)

○

240 m

○

C5



6.

|    |  |                |      |
|----|--|----------------|------|
|    |  |                |      |
| 1  |  | Ex d IIB T4 Gb | IE3  |
| 2  |  | VR             |      |
| 3  |  |                |      |
| 4  |  | Ex d IIB T4 Gb |      |
| 5  |  |                |      |
| 6  |  | (Ex d )        | IP55 |
| 7  |  |                |      |
| 8  |  | 30             | 10   |
| 9  |  |                |      |
| 10 |  |                |      |

7

7.1

7

7.2

---

7.3

- ☐
- ☐
- ☐
- ☐
- ☐

**8.**

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

8.2

---

9.

24

2

24

10

10.

10.1    5

10.2

